

# 15,000 LB. 4-POST LIFT

4115 MODEL\*



**NEW WIDER  
RUNWAYS**

## THE 4115 EXPERIENCE

Designed with productivity and safety in mind, our newly improved 15,000 lb 4-Post Lift would be a great addition to any shop floor. With several configurations available, you're sure to find the lift to meet your needs.

Increase your customer base with this lift as it can accommodate

and service a wide range of vehicles. Anything from a small passenger car to a medium-duty truck, and even medium-sized vans. All while boosting workplace safety with our open front design, assisting technicians moving around a vehicle's frame.



4-Post Flat Deck General Service and Alignment Rack  
Package 15,000 Lb. capacity

CHALLENGERLIFTS.COM

**CL Challenger Lifts**

# FEATURES & BENEFITS:

- All-new and wider 22" runways.
- Open and closed front design for **better ergonomics**, allowing **easy access to adjustment points** on both standard or long length runway racks.
- Improved 4-wheel alignment wheelbase for extended alignment capabilities allowing you to **service both long and short wheelbase vehicles**.
- Louvered approach ramps prevent wheelspin and are more effective than diamond tread or abrasive strips.
- Keep your shop looking **stylish & clean** with our new and improved all enclosed front column and crossbeam design. Expect a **longer and smoother operational life** with our UHMW internally encapsulated slide block.
- Compatible with the industry's latest imaging alignment systems.
- 17 locking positions with improved lock design.
- *Optional Alignment kit includes: rolling jacks, internal airline system, & stainless steel turn plates*

Model Number	4115EFO	4115XFO	4115EFX	4115XFX	AR4115EAO	AR4115XAO	AR4115EAX	AR4115XAX
Lifting Capacity	15,000 lbs.	15,000 lbs.	15,000 lbs.	15,000 lbs.	15,000 lbs.	15,000 lbs.	15,000 lbs.	15,000 lbs.
Open or Closed Front	Open	Open	Closed	Closed	Open	Open	Closed	Closed
A Overall Length	250.75"	277"	247.625"	275.5"	250.75"	277"	247.625"	275.5"
B Overall Width	142"	142"	142"	142"	142"	142"	142"	142"
C Inside Columns	Front: 120.75" Rear: 125.5"	Front: 120.75" Rear: 125.5"	125.5"	125.5"	Front: 120.75" Rear: 125.5"	Front: 120.75" Rear: 125.5"	125.5"	125.5"
D Between Columns	195"	222.5"	196"	223.375"	195"	222.5"	196"	223.375"
E Height of Columns	Front: 99.25" Rear: 98"	Front: 99.25" Rear: 98"	98"	98"	Front: 99.25" Rear: 98"	Front: 99.25" Rear: 98"	98"	98"
F Height of Runways	7"	7"	7"	7"	7"	7"	7"	7"
G Width of Runways	22.375"	22.375"	22.375"	22.375"	22.375"	22.375"	22.375"	22.375"
H Width Between Runways	40.625"	40.625"	40.625"	40.625"	40.625"	40.625"	40.625"	40.625"
i Max. Wheelbase <sup>1</sup>	183"	210.5"	183"	210.5"	183"	210.5"	183"	210.5"
J Rise Height	78"	78"	78"	78"	78"	78"	78"	78"
Max. 2 Wheel Alignment	N/A	N/A	N/A	N/A	167.75"	195.25"	167.75"	195.25"
Max. 4 Wheel Alignment	-	-	-	-	68" - 158"	68" - 158"	68" - 158"	68" - 158"
Air Supply Required	90-120 psi	90-120 psi	90-120 psi	90-120 psi	90-120 psi	90-120 psi	90-120 psi	90-120 psi
Motor / Voltage <sup>2</sup>	2HP, 208v-230v, 60Hz, 1Ph							
Rise Time	85 s	85 s	85 s	85 s	85 s	85 s	85 s	85 s
Min. Recomm. Bay Size	14' x 24'	14' x 26'	14' x 24'	14' x 26'	14' x 24'	14' x 26'	14' x 24'	14' x 26'

<sup>1</sup>Maximum wheelbase is based on a tire diameter of 30".

<sup>2</sup>Optional 3 phase electrical also available. Standard lift colors are Red, Blue or Black. Optional colors available.

